

Barbara Ann

2 Year Warranty

OUTPUT POWER @ 14.4V input		DAMPING FACTOR @100Hz 4 ohm	> 200
RMS per channel at 4 Ohms	100 W x 4 CH	CROSSOVER RANGE	CH 3&4, CH 1&2
RMS per channel at 2 Ohms	175 W x 4 CH	High Pass, 12dB/Octave	15-500 Hz, 50-3K Hz
RMS Bridged Mono at 4 Ohms	350 W x 2 CH	Low Pass, 24dB/Octave	55-3.5K Hz
RMS Mono at 1 Ohm	N/A	Subsonic	N/A
INPUT SENSITIVITY	200mV - 6.0V	Variable Bass Boost (0 to + 12 dB bass boost at 45 Hz)	Selectable 0/6/12 dB
FREQUENCY RESPONSE	10Hz - 30Hz +/- 0.5dB	Wired remote bass control included	No
THD	LESS THAN 0.01%	Phase Shift (0 - 180 degrees)	No
S/N RATIO	> 97 dB	Fusing	3 x 35A
CHANNEL SEPARATION	> 92 dB	Size (L x W x H) in	16.4 x 8.9 x 2.2

Beach'n Sound!

Features

- 4 x 100 Watts RMS @ 4 Ohm
- Angled Terminals for show quality installations
- Old School Full Complimentary low distortion Class AB design
- Butterworth Crossover Filters for serious high-end performance
- Docking Pads® to reduce vibration and extend the life of your amplifier
- DC, Short Circuit, Thermal and Overload Protection
- Diagnostic LEDs