

Mike

2 Year Warranty

OUTPUT POWER @ 14.4V input		DAMPING FACTOR @100Hz 4 ohm	> 250
RMS per channel at 4 Ohms	375 x 1 CH	CROSSOVER RANGE	
RMS per channel at 2 Ohms	750 x 1 CH	High Pass, 12dB/Octave	N/A
RMS Bridged Mono at 4 Ohms	N/A	Low Pass, 24dB/Octave	10Hz - 150Hz
RMS Mono at 1 Ohm	1500 x 1 CH	Subsonic	15Hz - 55Hz
INPUT SENSITIVITY	200mV - 6.0V	Variable Bass Boost (0 to +12 dB bass boost at 50 Hz)	Yes
FREQUENCY RESPONSE	10Hz - 150Hz +/- 0.5dB	Wired remote bass control included	Yes
THD	LESS THAN 0.1%	Phase Shift (0 - 180 degrees)	No
S/N RATIO	> 101 dB	Fusing	4 x 40A
CHANNEL SEPARATION	N/A	Size (L x W x H) in	14.1 x 8.9 x 2.2

Everybody Likes Mike!

Features

- 1 x 1500 Watts RMS @ 1 Ohm
- Thermally Stable Heat Sink design for maximum heat transfer efficiency
- Extra Large Gauge Terminals for show quality installations
- Extreme Bulk capacitor banks for High Power Stability
- Designed with the latest Technology in Ultra Efficient Class D design
- Butterworth Crossover Filters for serious high-end performance
- Docking Pads® to reduce vibration and extend the life of your amplifier
- DC, Short Circuit, Thermal and Overload Protection
- Diagnostic LEDs