

Sound Supremacy!

TONY

Limited 1 Year Warranty

OUTPUT POWER @ 14.4 V INPUT	Less than 1% THD	DAMPING FACTOR @100 HZ 4 OHM	Greater than 300
RMS PER CHANNEL AT 4 OHMS	1500 W x 1 CH	CROSSOVER RANGE	
RMS PER CHANNEL AT 2 OHMS	3000 W x 1 CH	LOW PASS, 24 DB/OCTAVE	35 Hz - 250 Hz
RMS BRIDGED MONO AT 4 OHMS	N/A	SUBSONIC	10 Hz - 50 Hz
RMS MONO AT 1 OHM	6000 W x 1 CH	WIRED REMOTE BASS CONTROL INCLUDED	Yes
INPUT SENSITIVITY	200 mV - 6.0 V	PHASE SHIFT (0 - 180 DEGREES)	Yes
FREQUENCY RESPONSE	14 Hz - 248 Hz +/- 1 dB	FUSING (NOT SUPPLIED)	External 570 A
S/N RATIO	< 95 dB	SIZE (L X W X H) IN	27.75 x 8.7 x 2.72
EFFICIENCY (4Ω, 100 HZ)	< 95%		

Features

- 1 x 6000 Watts RMS @ 1 Ohm
- Thermally Stable Heat Sink design for maximum heat transfer efficiency
- 3 x 0 Gauge Power + Ground Input Connectors
- Extreme Bulk capacitor banks for High Power Stability
- Designed with the latest Technology in Ultra Efficient Class D design
- DC, Short Circuit, Thermal and Overload Protection
- Diagnostic LEDs
- Clipping LED Indicator