

Barbara Ann

2 Year Warranty

OUTPUT POWER @ 14.4V input		DAMPING FACTOR @100Hz 4 ohm	> 200
RMS per channel at 4 Ohms	100 W x 4 CH	CROSSOVER RANGE	CH 3&4, CH 1&2
RMS per channel at 2 Ohms	175 W x 4 CH	High Pass, 12dB/Octave	15 -150 Hz (X1) 150 - 1.5 KHz (X10)
RMS Bridged Mono at 4 Ohms	350 W x 2 CH	Low Pass, 24dB/Octave	50 - 500 Hz (X1) 500 - 5K Hz (X10)
RMS Mono at 1 Ohm	N/A	Band Pass	N/A
INPUT SENSITIVITY	200mV - 6.0V	Variable Bass Boost (0 to +12 dB bass boost at 45 Hz)	-
FREQUENCY RESPONSE	10Hz - 30Hz +/- 0.5dB	Wired remote bass control included	No
THD	LESS THAN 0.01%	Phase Shift (0 - 180 degrees)	No
S/N RATIO	> 97 dB	Fusing	3 x 30A
CHANNEL SEPARATION	> 92 dB	Size (L x W x H) in	17.7 x 8.9 x 2.2

Beach'n Sound!

Features

- 4 x 100 Watts RMS @ 4 Ohm
- Angled Terminals for show quality installations
- Old School Full Complimentary low distortion Class AB design
- Butterworth Crossover Filters for serious high-end performance
- DC, Short Circuit, Thermal and Overload Protection
- Diagnostic LEDs
- Audiophile Hi End Op Amps