

Mai

2 Year Warranty

OUTPUT POWER @ 14.4V input	CH 1&2, CH 3&4	DAMPING FACTOR @100Hz 4 ohm	> 100
RMS per channel at 4 Ohms	50 W x 4 CH	CROSSOVER RANGE	CH 3&4, CH 1&2
RMS per channel at 2 Ohms	80 W x 4 CH	High Pass, 12dB/Octave	20 Hz - 3K Hz, CH 1&2 15 Hz-1.5K Hz, CH 3&4
RMS Bridged Mono at 4 Ohms	160 W x 2 CH	Low Pass, 24dB/Octave	50 Hz - 5K Hz, CH 3&4
CH 5 RMS per channel at 1 Ohm	300 W x 1 CH	Low Pass, 24dB/Octave	50 Hz - 500 Hz, CH 5
INPUT SENSITIVITY	200mV - 6.0V	Variable Bass Boost (0 to +12 dB bass boost at 45 Hz)	No
FREQUENCY RESPONSE	10Hz - 22Hz +/- 0.5dB	Wired remote bass control included	No
THD	LESS THAN 0.5%	Phase Shift (0 - 180 degrees)	No
S/N RATIO	> 96 dB	Fusing	1 x 70A
CHANNEL SEPARATION	>70 dB	Size (L x W x H) in	11.41 x 4.68 x 2.04

A Portrait of Audio Performance!

Features

- 4 x 50 Watts RMS @ 4 Ohm
- Compact Design for Smaller Installation Footprint
- Angled Terminals for show quality installations
- Full Range Class D Design
- Conformal Coated Printed Circuit Board for Marine and Motorcycle Applications
- DC, Short Circuit, Thermal and Overload Protection
- Diagnostic LEDs